



CERAMIC INFRARED HEATERS

FSR SERIES (Proved Quality)

- a) 245mm x 60mm - 250 W to 1000 W
 - b) 122mm x 60mm - 125 W to 500 W
 - c) 60mm x 60mm - 60 W to 250 W
- Temperature: up to 720°C
Max. watt density: 64.0 kW/m²
Wavelength: 2-10 μm

CERAMIC INFRARED HEATERS



HTS SERIES (ENERGY SAVING)

- a) 122mm x 122 mm - 250 W to 1000 W
 - b) 245mm x 60 mm - 250 W to 1000 W
 - c) 122mm x 60 mm - 125 W to 500 W
 - d) 60mm x 60 mm - 60 W to 250 W
- Temperature: up to 860°C
Max. watt density: 64.0 kW/m²
Wavelength: 2-10 μm



FSF SERIES

- a) 122mm x 122 mm - 250 W to 1000 W
 - b) 245mm x 60 mm - 250 W to 1000 W
 - c) 122mm x 60 mm - 125 W to 500 W
 - d) 60mm x 60 mm - 60 W to 250 W
- Temperature: up to 720°C
Max. watt density: 64.0 kW/m²
Wavelength: 2-10 μm



EBF SERIES (ENERGY SAVING)

- a) 100mm x 250mm
 - b) 100mm x 1250 mm
 - c) Other lengths on request
- Temperature: up to 860°C
Max. watt density: 48.0 kW/m²
Wavelength: 2-10 μm



BSI SERIES (IR SYSTEM)

- 125mm x 250mm up to 1000mm x 1500 mm
 - Other sizes on request
- Temperature: up to 860°C
Max. watt density: 64.0 kW/m²
Wavelength: 2-10 μm

